



Application

- Portable Sound Reinforcement
- Foreground and Background Music Applications

Features

- Double 15 Inch woofers for high sound power output and deep bass.
- True 34mm compression driver for high system reliability and high intelligibility.

The P.Audio XE-215 provides a cost effective foreground sound reinforcement solution to both portable and fixed install applications. The double 15" woofers provide high intelligibility and extended low frequency response in a convenient, medium profile design. The XE-215 is ideal for foreground full range music systems, as well as fill speakers in touring systems. The 34mm true compression driver in the XE-215 features very high reliability, and is coupled to a 60 x 40 degree medium to long throw horn for controlled and detailed high frequency performance.

The quasi-three way passive network in XE-215 balances the output from all transducer components and provides optimal summing in the mid band region. The power handling is rated at 600 watts continuous with a peak input power of 2400 watts.

Cabinet construction is of high quality plywood with internal supports for extra rigidity, and is finished with high quality black paint. The XE-215 is a high performance design with superior vocal intelligibility from the high quality P.Audio components.

General Specifications

Type	Passive 2.5 Way
Woofer Size	2 x 15"
Woofer Voice Coil	2.5"
HF Size	1"
HF Voice Coil	1.3"
Cabinet design	Plywood
Handles	6
Pole Mount	None
Weight	41.2 kg / 90.8 lbs
Dimensions (WxDxH)	479.8x476.6x1170 mm / 18.9x18.8x46.1 in

Acoustic Specifications

Sensitivity (1w/1m) (dB)	97dB
-3dB Response	45Hz - 18kHz
-10dB Response	40Hz - 20kHz
Power Handling (Watt)	600w Continuous (2400w Peak)
Maximum Continuous SPL (dB)	125dB
Maximum Peak SPL (dB)	129dB
Dispersion (HxV)	60 x 40

Electrical Specifications

Impedance	4 Ohm
Input	Speakon
Thru	Speakon